

## HE574 - BLUESKIN LVC ADHESIVE

P.A.R.A. : 2,2.05,B

Last Rev Date: 10/23/2009

### Physical Properties

Application Temperature -12°F to 104°F	Drying Time (Set through) 2 hours	Service Temperature -40°F to 158°F
Color Blue	Flammability Wet - Flammable, Dry - Burns	Solids By Weight 40%
Drying Time (Initial set) Approx. 30 minutes	Maximum VOC <240 g/l	Weight Per Gallon 7.68 lbs.

### Description

HE574 - BLUESKIN LVC ADHESIVE is a quick drying, lower volatile organic compound (VOC) formulation, rubber based adhesive designed to enhance the adhesion of self-adhesive membranes such as Blueskin®.

#### Features:

- Compliant with OTC rules for industrial adhesives and sealants and California South Coast Rule 1168
- Quick setting
- Aggressive tack provides improved adhesion of membrane to substrate
- Suitable for application at normal and low temperatures
- Easily applied

### Usage

Used as an adhesive for self-adhesive membranes such as Blueskin® SA, SALT, TWF, VP and WP200 when applied to masonry, concrete, wood, gypsum board, DensGlass™ Gold and metal surfaces. HE574 - BLUESKIN LVC ADHESIVE is the surface preparation of choice on above grade applications of self-adhered membranes where a quick setting, aggressive tack, solvent based primer is required.

Limitations: Avoid direct application on polystyrene materials, such as polystyrene insulation boards. Avoid use and exposure to open flames, electrical discharges and other ignition sources or where solvent odors may taint food or other susceptible products.

### Coverage

Up to 250 sq. ft./ US gal depending on porosity and texture of surface.

### Surface Preparation

Surfaces must be dry and free from dust, dirt, grease, oil or other foreign matter.

### Application

BLUESKIN LVC ADHESIVE may be applied by brush, roller or spray at up to 250 sq. ft./US gal. Rollers should have a solvent-resistant heavy nap of natural materials such as lamb's wool. Allow adhesive to dry for approximately 30 minutes, longer under cold conditions, before applying membrane. Coated surfaces not covered by membrane during the working day must be recoated.

### Cleanup

Remove from tools, etc. with mineral spirits. Clean hands with a waterless hand cleaner.

### Caution

**DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPORS MAY CAUSE FLASH FIRE.** Contains hexane, methyl

acetate, and p-chlorobenzotrifluoride. Vapors may ignite explosively. Keep away from heat, sparks and flame. Vapors may cause flash fire. Do not smoke. Extinguish all flames and pilot lights; turn off all stoves, heaters, electric motors, and other sources of ignition during use and until all vapors are gone. Do not heat container or store at temperatures greater than 120°F.

FOR EXTERIOR USE ONLY!

KEEP OUT OF REACH OF CHILDREN!

CLOSE AIR INTAKES until solvents dissipate. Contains volatile solvents that might contaminate potable water. Close container after each use.

DANGER! HARMFUL OR FATAL IF SWALLOWED. IF SWALLOWED, DO NOT INDUCE VOMITING. CALL PHYSICIAN IMMEDIATELY! May be harmful if absorbed through skin. Use protective measures to avoid contact with eyes and skin. In case of eye contact, open eyelids wide and flush immediately with plenty of water for at least 15 minutes. GET MEDICAL ATTENTION! USE ONLY WITH ADEQUATE VENTILATION! Avoid breathing of vapor. If you experience eye watering, headaches or dizziness, leave area or increase fresh air or wear respirator (NIOSH/MSHA TC 23C or equal). Repeated and prolonged occupational exposure to solvents can result in permanent brain and nervous system damage.

#### Product Sizes

4.5 GAL/17 L w/SPOUT (40 lb)

#### Limited Warranty

We, the manufacturer, warrant only that this product is free of defects, since many factors which affect the results obtained from this product - such as weather, workmanship, equipment utilized and prior condition of the substrate - are all beyond our control. We will replace at no charge any product proved to be defective within 12 months of purchase, provided it has been applied in accordance with our written directions for uses we recommended as suitable for this product. Proof of purchase must be provided. DISCLAIMER OF WARRANTIES AND LIMITATION OF LIABILITY: THIS LIMITED WARRANTY IS IN LIEU OF ANY OTHER WARRANTIES EXPRESS OR IMPLIED INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FOR A PARTICULAR PURPOSE. MANUFACTURER SHALL HAVE NO LIABILITY OF ANY KIND BEYOND PRODUCT REPLACEMENT, INCLUDING FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES RESULTING FROM ANY DEFECTS OR ANY DELAYS CAUSED BY REPLACEMENT OR OTHERWISE. THIS LIMITED WARRANTY PROVIDES THE PURCHASER'S EXCLUSIVE REMEDY FOR ANY DEFECT IN THE PRODUCT.